



230-2510 SPR Sealing Plugs



Cat. No.	O. D.			Length C mm	Std. Pkg. pcs
	Black	A mm	B mm		
SPR - 055A - B	11	5.5	8.7	18	100
SPR - 055B - B	9.6	5.5	7.1	18	100
SPR - 067 - B	9.5	6.7	7.2	18	100
SPR - 071 - B	13.2	7	10.7	18	100
SPR - 079 - B	11	7.9	8.7	18	100
SPR - 092 - B	15.5	9.2	12.7	18	100
SPR - 103 - B	13.5	10.3	10.7	18	100
SPR - 105 - B	17	10.5	14.3	18	100
SPR - 118 - B	17	11.8	14.3	18	100
SPR - 120 - B	15.5	12	12.7	18	100
SPR - 140 - B	17	14	14.4	18	100
SPR - 158 - B	22	15.8	19.3	18	50
SPR - 178 - B	22	17.8	19.3	18	50
SPR - 215 - B	28	21.5	25	18	50
SPR - 245 - B	28	24.5	25	18	50
SPR - 262 - B	35	26.2	33	20	10
SPR - 306 - B	36	30.6	33	20	10
SPR - 333 - B	45	33.3	43.1	20	10
SPR - 410 - B	46	41	43.1	20	10
SPR - 473 - B	53	47.3	51.6	20	10
SPR - 515 - B	54.5	51.5	-	20	10

- Material : Standard in weather-resistant EPDM rubbers ;
* NBR rubber is optional for oil-resistance applications.
- Color : Black.
- Application : For all kind of devices and machines where the cable connection are installed later, seal the spare cable glands against dust and water from entering the housings.

230-2520 SPM Sealing Pins



Cat. No.	O. D.		Length C mm	Std. Pkg. pcs
	Black	A mm		
SPM - 020 - B	3	2	15	100
SPM - 023 - B	3	2.3	15	100
SPM - 026 - B	3.6	2.6	15	100
SPM - 030 - B	4	3	15	100
SPM - 032 - B	4.2	3.2	15	100
SPM - 034 - B	4.4	3.4	15	100
SPM - 037 - B	4.7	3.7	15	100
SPM - 041 - B	5.1	4.1	15	100
SPM - 050 - B	6	5	15	100
SPM - 053 - B	6.3	5.3	15	100
SPM - 060 - B	7.5	6	15	100
SPM - 070 - B	8.5	7	15	100
SPM - 073 - B	8.5	7.3	15	100
SPM - 080 - B	9.5	8	15	100
SPM - 090 - B	10.5	9	15	100
SPM - 100 - B	11.5	10	15	100

- Material : Standard in weather-resistant EPDM rubbers ;
* NBR rubber is optional for oil-resistance applications.
- Color : Black.
- Application : For AVC's Multiple Sealing Inserts, when the cable connection is installed later or some spare holes are unneeded, seal the spare holes to prevent dusts and waters from entering the housings.