



PCB Layout Dimension (Tolerance: ±0.10)
(Recommend min. Dimension)(Bottom View)

Note : Approved Standard: VDE File No.:1550600-1550-0006/120908
SEMKO Reference No.:1000039
CB certificate No.:DE1-47360

8	PIN	2	C2680	t=0.40	MBCu2 μ m-Sn3 μ m
7	SHUNT SPRING(B)	1	C2680	t=0.30	MBCu2 μ m-Ag0.6 μ m
6	TIP SPRING	1	C5191	t=0.30	MBCu2 μ m-Ag0.6 μ m
5	SHUNT SPRING(A)	1	C5191	t=0.30	MBCu2 μ m-Ag0.6 μ m
4	SEPARATOR	1	PBT		SHINKONG D202
3	BASE	1	PPO	UL 94V-0	SABIC RESIN(Black)
2	COVER	1	PPO	UL 94V-0	SABIC RESIN(Black)
1	HOUSING	1	PBT+30%GF	UL 94V-0	SHINKONG D202G30(Black)

LTR	PART NAME	Q'TY	MATERIAL	REMARK
120~315	±0.5	DWN	劉怡廷	DATE 1996.05.28
30~120	±0.35	DSND	CHUNG CHEN	DATE 1996.05.27
6~30	±0.22	CHKD	劉怡廷	DATE 1997.10.29
BELOW 6	±0.16	APVD	龔雲輝	DATE 1997.10.29
DIMENSION	TOLERANCE	KUNMING ELECTRONICS CO.,LTD.		

SCALE 1.25/1
PROJECTION
UNIT: mm

NAME AC POWER SOCKET
CAT. NO. HJC-020-P
DWN.NO. A-020-P
1/1
H

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.30 ANGLES: ±5°

REVISIONS					
LTR	DESCRIPTION	DATE	REV.	CHKD.	APVD.
△x1	To modify the material (ECR No.C03110318)	2011.08.19	黃健璋	郭素玲	郭素玲
△x2	To correct name of manufacturer.(C03110372)	2012.01.05	黃健璋	郭素玲	郭遠峰