

<Hybrid-SiC Modules>

# CMH400DU-24NFH

HIGH POWER SWITCHING USE  
INSULATED TYPE



dual switch (Half-Bridge)

Collector current  $I_C$  ..... 400 A  
 Collector-emitter voltage  $V_{CES}$  ..... 1200 V  
 Maximum junction temperature  $T_{jmax}$  ..... 150 °C


- Silicon IGBT + Silicon Carbide Schottky Barrier Diode
- Flat base Type
- Copper base plate
- RoHS Directive compliant
- Recognized under UL1557, File E323585

**APPLICATION**

High frequency switching use(30kHz to 60kHz)  
 Gradient magnetic power supply, Induction heating, etc.


**OUTLINE DRAWING & INTERNAL CONNECTION**

Dimension in mm



Tolerance otherwise specified

| Division of Dimension | Tolerance |
|-----------------------|-----------|
| 0.5 to 3              | ±0.2      |
| over 3 to 6           | ±0.3      |
| over 6 to 30          | ±0.5      |
| over 30 to 120        | ±0.8      |
| over 120 to 400       | ±1.2      |



# CMH400DU-24NFH

HIGH POWER SWITCHING USE  
INSULATED TYPE

MAXIMUM RATINGS ( $T_j=25\text{ }^\circ\text{C}$ , unless otherwise specified, per 1/2 module)

| Symbol            | Item                      | Conditions                                                | Rating     | Unit             |
|-------------------|---------------------------|-----------------------------------------------------------|------------|------------------|
| $V_{CES}$         | Collector-emitter voltage | G-E short-circuited                                       | 1200       | V                |
| $V_{GES}$         | Gate-emitter voltage      | C-E short-circuited                                       | $\pm 20$   | V                |
| $I_C$             | Collector current         | DC, $T_C=25\text{ }^\circ\text{C}$ (Note2, 4)             | 400        | A                |
| $I_{CRM}$         |                           | Pulse, Repetitive (Note3)                                 | 800        |                  |
| $P_{tot}$         | Total power dissipation   | $T_C=25\text{ }^\circ\text{C}$ (Note2, 4)                 | 2450       | W                |
| $I_E$ (Note1)     | Emitter current           | DC, $T_C=25\text{ }^\circ\text{C}$ (Note2, 4)             | 400        | A                |
| $I_{ERM}$ (Note1) |                           | Pulse, Repetitive (Note3)                                 | 800        |                  |
| $V_{isol}$        | Isolation voltage         | Terminals to base plate, RMS, $f=60\text{ Hz}$ , AC 1 min | 4000       | V                |
| $T_j$             | Junction temperature      | -                                                         | -40 ~ +150 | $^\circ\text{C}$ |
| $T_{stg}$         | Storage temperature       | -                                                         | -40 ~ +125 |                  |

ELECTRICAL CHARACTERISTICS ( $T_j=25\text{ }^\circ\text{C}$ , unless otherwise specified, per 1/2 module)

| Symbol            | Item                                 | Conditions                                                                                                     | Limits                          |      |      | Unit          |   |
|-------------------|--------------------------------------|----------------------------------------------------------------------------------------------------------------|---------------------------------|------|------|---------------|---|
|                   |                                      |                                                                                                                | Min.                            | Typ. | Max. |               |   |
| $I_{CES}$         | Collector-emitter cut-off current    | $V_{CE}=V_{CES}$ , G-E short-circuited                                                                         | -                               | -    | 21.0 | mA            |   |
| $I_{GES}$         | Gate-emitter leakage current         | $V_{GE}=V_{GES}$ , C-E short-circuited                                                                         | -                               | -    | 1.4  | $\mu\text{A}$ |   |
| $V_{GE(th)}$      | Gate-emitter threshold voltage       | $I_C=40\text{ mA}$ , $V_{CE}=10\text{ V}$                                                                      | 4.5                             | 6.0  | 7.5  | V             |   |
| $V_{CESat}$       | Collector-emitter saturation voltage | $I_C=400\text{ A}$ , $V_{GE}=15\text{ V}$ (Note5)<br>Refer to the figure of test circuit                       | $T_j=25\text{ }^\circ\text{C}$  | -    | 5.0  | 6.5           | V |
|                   |                                      |                                                                                                                | $T_j=125\text{ }^\circ\text{C}$ | -    | 5.0  | -             |   |
| $C_{ies}$         | Input capacitance                    | $V_{CE}=10\text{ V}$ , G-E short-circuited                                                                     | -                               | -    | 63   | nF            |   |
| $C_{oes}$         | Output capacitance                   |                                                                                                                | -                               | -    | 5.3  |               |   |
| $C_{res}$         | Reverse transfer capacitance         |                                                                                                                | -                               | -    | 1.2  |               |   |
| $Q_G$             | Gate charge                          | $V_{CC}=600\text{ V}$ , $I_C=400\text{ A}$ , $V_{GE}=15\text{ V}$                                              | -                               | 1800 | -    | nC            |   |
| $t_{d(on)}$       | Turn-on delay time                   | $V_{CC}=600\text{ V}$ , $I_C=400\text{ A}$ , $V_{GE}=\pm 15\text{ V}$ ,<br>$R_G=0.78\ \Omega$ , Inductive load | -                               | -    | 300  | ns            |   |
| $t_r$             | Rise time                            |                                                                                                                | -                               | -    | 100  |               |   |
| $t_{d(off)}$      | Turn-off delay time                  |                                                                                                                | -                               | -    | 500  |               |   |
| $t_f$             | Fall time                            |                                                                                                                | -                               | -    | 150  |               |   |
| $V_{EC}$ (Note1)  | Emitter-collector voltage            | $I_E=400\text{ A}$ , G-E short-circuited (Note5)<br>Refer to the figure of test circuit                        | $T_j=25\text{ }^\circ\text{C}$  | -    | 1.7  | 2.2           | V |
|                   |                                      |                                                                                                                | $T_j=125\text{ }^\circ\text{C}$ | -    | 2.2  | -             |   |
| $Q_C$ (Note1)     | Total capacitive charge              | $V_{CC}=600\text{ V}$ , $I_E=400\text{ A}$ , $V_{GE}=\pm 15\text{ V}$ ,<br>$R_G=0.78\ \Omega$ , Inductive load | -                               | 3.3  | -    | $\mu\text{C}$ |   |
| $E_{on}$          | Turn-on switching energy per pulse   | $V_{CC}=600\text{ V}$ , $I_C/I_E=400\text{ A}$ ,<br>$V_{GE}=\pm 15\text{ V}$ , $R_G=0.78\ \Omega$ ,            | -                               | 6.5  | -    | mJ            |   |
| $E_{off}$         | Turn-off switching energy per pulse  |                                                                                                                | -                               | 16.0 | -    |               |   |
| $E_{rec}$ (Note1) | Reverse energy per pulse             | $T_j=125\text{ }^\circ\text{C}$ , Inductive load                                                               | -                               | 1.3  | -    | mJ            |   |
| $r_g$             | Internal gate resistance             | Per switch                                                                                                     | -                               | 0.8  | -    | $\Omega$      |   |

THERMAL RESISTANCE CHARACTERISTICS (per 1/2 module)

| Symbol         | Item                       | Conditions                                           | Limits |      |       | Unit |
|----------------|----------------------------|------------------------------------------------------|--------|------|-------|------|
|                |                            |                                                      | Min.   | Typ. | Max.  |      |
| $R_{th(j-c)Q}$ | Thermal resistance         | Junction to case (Note4)                             | -      | -    | 0.051 | K/W  |
| $R_{th(j-c)D}$ |                            | Junction to case (Note4)                             | -      | -    | 0.123 |      |
| $R_{th(c-s)}$  | Contact thermal resistance | Case to heat sink, Thermal grease applied (Note4, 6) | -      | 0.02 | -     | K/W  |

Caution; No short-circuit capability is designed.

# CMH400DU-24NFH


HIGH POWER SWITCHING USE  
INSULATED TYPE

## MECHANICAL CHARACTERISTICS

| Symbol | Item                   | Conditions                                 | Limits |      |      | Unit          |
|--------|------------------------|--------------------------------------------|--------|------|------|---------------|
|        |                        |                                            | Min.   | Typ. | Max. |               |
| $M_t$  | Mounting torque        | Main terminals M 6 screw                   | 3.5    | 4.0  | 4.5  | N·m           |
| $M_s$  | Mounting torque        | Mounting to heat sink M 6 screw            | 3.5    | 4.0  | 4.5  | N·m           |
| $d_s$  | Creepage distance      | Terminal to terminal                       | 17.0   | -    | -    | mm            |
|        |                        | Terminal to base plate                     | 32.0   | -    | -    |               |
| $d_a$  | Clearance              | Terminal to terminal                       | 11.0   | -    | -    | mm            |
|        |                        | Terminal to base plate                     | 28.1   | -    | -    |               |
| $m$    | mass                   | -                                          | -      | 580  | -    | g             |
| $e_c$  | Flatness of base plate | On the centerline X <small>(Note7)</small> | -100   | -    | 100  | $\mu\text{m}$ |
|        |                        | On the centerline Y <small>(Note7)</small> | -100   | -    | 100  |               |

\*: This product is compliant with the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment (RoHS) directive 2011/65/EU.

- Note1. Represent ratings and characteristics of the anti-parallel, emitter-collector free-wheeling diode (DIODE).  
 2. Junction temperature ( $T_j$ ) should not increase beyond  $T_{jmax}$  rating.  
 3. Pulse width and repetition rate should be such that the device junction temperature ( $T_j$ ) dose not exceed  $T_{jmax}$  rating.  
 4. Case temperature ( $T_c$ ) and heat sink temperature ( $T_s$ ) are defined on the each surface (mounting side) of base plate and heat sink just under the chips.  
 Refer to the figure of chip location.  
 5. Pulse width and repetition rate should be such as to cause negligible temperature rise.  
 6. Typical value is measured by using thermally conductive grease of  $\lambda=0.9 \text{ W/(m}\cdot\text{K)}$ .  
 7. The base plate (mounting side) flatness measurement points (X, Y) are as follows of the following figure.




## RECOMMENDED OPERATING CONDITIONS

| Symbol     | Item                          | Conditions                             | Limits |      |      | Unit     |
|------------|-------------------------------|----------------------------------------|--------|------|------|----------|
|            |                               |                                        | Min.   | Typ. | Max. |          |
| $V_{CC}$   | (DC) Supply voltage           | Applied across C1-E2 terminals         | -      | 600  | 800  | V        |
| $V_{GEon}$ | Gate (-emitter drive) voltage | Applied across G1-Es1/G2-Es2 terminals | 13.5   | 15.0 | 16.5 | V        |
| $R_G$      | External gate resistance      | Per switch                             | 0.78   | -    | 7.8  | $\Omega$ |

## CHIP LOCATION (Top view)

Dimension in mm, tolerance:  $\pm 1 \text{ mm}$






Tr1/Tr2: IGBT, Di1/Di2: DIODE

# CMH400DU-24NFH


HIGH POWER SWITCHING USE  
INSULATED TYPE

## TEST CIRCUIT AND WAVEFORMS




Switching test circuit and waveforms


$t_{rr}$ ,  $Q_{rr}$  test waveform



IGBT Turn-on switching energy




IGBT Turn-off switching energy



DIODE Reverse recovery energy


Turn-on / Turn-off switching energy and Reverse recovery energy test waveforms (Integral time instruction drawing)

## TEST CIRCUIT




Tr1

$V_{CEsat}$  characteristics test circuit




Tr2



Di1

$V_{EC}$  characteristics test circuit




Di2

# CMH400DU-24NFH


HIGH POWER SWITCHING USE  
INSULATED TYPE

## PERFORMANCE CURVES


OUTPUT CHARACTERISTICS (TYPICAL)




COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)



COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)



FREE WHEELING DIODE FORWARD CHARACTERISTICS (TYPICAL)




# CMH400DU-24NFH

HIGH POWER SWITCHING USE  
INSULATED TYPE

## PERFORMANCE CURVES


HALF-BRIDGE  
SWITCHING CHARACTERISTICS  
(TYPICAL)

$V_{CC}=600\text{ V}$ ,  $V_{GE}=\pm 15\text{ V}$ ,  $R_G=0.78\ \Omega$ ,  
 $T_j=125\text{ }^\circ\text{C}$ , INDUCTIVE LOAD




HALF-BRIDGE  
SWITCHING CHARACTERISTICS  
(TYPICAL)

$V_{CC}=600\text{ V}$ ,  $V_{GE}=\pm 15\text{ V}$ ,  $I_C=400\text{ A}$ ,  
 $T_j=125\text{ }^\circ\text{C}$ , INDUCTIVE LOAD




HALF-BRIDGE  
SWITCHING CHARACTERISTICS  
(TYPICAL)

$V_{CC}=600\text{ V}$ ,  $V_{GE}=\pm 15\text{ V}$ ,  $R_G=0.78\ \Omega$ ,  $T_j=125\text{ }^\circ\text{C}$ ,  
INDUCTIVE LOAD, PER PULSE



HALF-BRIDGE  
SWITCHING CHARACTERISTICS  
(TYPICAL)

$V_{CC}=600\text{ V}$ ,  $V_{GE}=\pm 15\text{ V}$ ,  $I_C/I_E=400\text{ A}$ ,  $T_j=125\text{ }^\circ\text{C}$ ,  
INDUCTIVE LOAD, PER PULSE




# CMH400DU-24NFH


HIGH POWER SWITCHING USE  
INSULATED TYPE

## PERFORMANCE CURVES


CAPACITANCE CHARACTERISTICS (TYPICAL)




FREE WHEELING DIODE REVERSE RECOVERY CHARACTERISTICS (TYPICAL)



GATE CHARGE CHARACTERISTICS (TYPICAL)



TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (MAXIMUM)



Note: The characteristics curves are presented for reference only and not guaranteed by production test, unless otherwise noted.

# CMH400DU-24NFH

HIGH POWER SWITCHING USE

INSULATED TYPE

## **Keep safety first in your circuit designs!**

Mitsubishi Electric Corporation puts the maximum effort into making semiconductor products better and more reliable, but there is always the possibility that trouble may occur with them. Trouble with semiconductors may lead to personal injury, fire or property damage. Remember to give due consideration to safety when making your circuit designs, with appropriate measures such as (i) placement of substitutive, auxiliary circuits, (ii) use of non-flammable material or (iii) prevention against any malfunction or mishap.

## **Notes regarding these materials**

- These materials are intended as a reference to assist our customers in the selection of the Mitsubishi semiconductor product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Mitsubishi Electric Corporation or a third party.
- Mitsubishi Electric Corporation assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.
- All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Mitsubishi Electric Corporation without notice due to product improvements or other reasons. It is therefore recommended that customers contact Mitsubishi Electric Corporation or an authorized Mitsubishi Semiconductor product distributor for the latest product information before purchasing a product listed herein.  
The information described here may contain technical inaccuracies or typographical errors. Mitsubishi Electric Corporation assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors.  
Please also pay attention to information published by Mitsubishi Electric Corporation by various means, including the Mitsubishi Semiconductor home page ([www.MitsubishiElectric.com/semiconductors/](http://www.MitsubishiElectric.com/semiconductors/)).
- When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Mitsubishi Electric Corporation assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.
- Mitsubishi Electric Corporation semiconductors are not designed or manufactured for use in a device or system that is used under circumstances in which human life is potentially at stake. Please contact Mitsubishi Electric Corporation or an authorized Mitsubishi Semiconductor product distributor when considering the use of a product contained herein for any specific purposes, such as apparatus or systems for transportation, vehicular, medical, aerospace, nuclear, or undersea repeater use.
- The prior written approval of Mitsubishi Electric Corporation is necessary to reprint or reproduce in whole or in part these materials.
- If these products or technologies are subject to the Japanese export control restrictions, they must be exported under a license from the Japanese government and cannot be imported into a country other than the approved destination.  
Any diversion or reexport contrary to the export control laws and regulations of Japan and/or the country of destination is prohibited.
- Please contact Mitsubishi Electric Corporation or an authorized Mitsubishi Semiconductor product distributor for further details on these materials or the products contained therein.